System SF55c



🗌 Inquiry 🔲 Or	der	Customer number:	
Company stamp / address:		Contact person:	
		Telephone:	
		Quotation No.:	
		Commission:	
Type of timber and finish:			
Number of systems:			
Opening direction: inwards folding outwards folding (Note: Use interior view!)			
Number of panel to the left to the right (Please draw a floor plan or a view sketch for better understanding)			
Dimensions: Width:	(Total unfolding)	Height: (ir	cl. possible floor recession)
Colour: RAL 7016	RAL 9006 RAL 9007	RAL 9016 🗌 E6-EV1	Special colour Pre anodizing
Colour of hinges:	E6-EV1 powder RAL 901	1 mat 🗌 RAL 9016	Special colour
Handle colour:	E6-EV1 powder RAL 901	1 mat 🗌 RAL 9016	Special colour
Handle height: H = (Indicate handle height from lower panel edge)			
Glazing:	 Standard heat protection glass 2 x 4 without glass: prepared for Special glass: 	mm	exact designation)
Floor connection:	with weathered bottom track		
	with flush bottom track (height incl	. floor recession)	
ocking of turn panel: Standard (shoot bolt lock operated from inside only) only possible with an add number of panels Shoot bolt lock with PZ (operated from both sides) Roller latch + 2 x dead lock + HEWI push handle Anti-draft lock with mushroom head and 4 point locking, latch and profile cylinder (operable on both sides) Pull handle for turn panel, outward folding system other:			
Additional safety:	Twin-Lock RC2-Safety package		

Please enclose floor plan resp. view sketch and remarks (please use inside view)